Data Mining
Classification: Basic Concepts and Techniques

Lecture Notes for Chapter 3

Introduction to Data Mining, 2nd Edition

by

Tan, Steinbach, Karpatne, Kumar


Classification: Definition

- Given a collection of records (training set)
  - Each record is by characterized by a tuple ($\boldsymbol{x}$,y), where $\boldsymbol{x}$ is the attribute set and y is the class label
    - $\boldsymbol{x}$: attribute, predictor, independent variable, input
    - y: class, response, dependent variable, output
- Task:
  - Learn a model that maps each attribute set $\boldsymbol{x}$ into one of the predefined class labels y

Examples of Classification Task

Task	Attribute set, x	Class label, y
Categorizing email messages	Features extracted from email message header and content	spam or non-spam
Identifying tumor cells	Features extracted from x-rays or MRI scans	malignant or benign cells
Cataloging galaxies	Features extracted from telescope images	Elliptical, spiral, or irregular-shaped galaxies

General Approach for Building Classification Model



ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
11	No	Married	55K	?
12	Yes	Divorced	80K	?
13	Yes	Single	110K	?
14	No	Single	95K	?
15	No	Married	67K	?

Figure 3.3. General framework for building a classification model.


Classification Techniques

- Base Classifiers
  - Decision Tree based Methods
  - Rule-based Methods
  - Nearest-neighbor
  - Naïve Bayes and Bayesian Belief Networks
  - Support Vector Machines
  - Neural Networks, Deep Neural Nets
- Ensemble Classifiers
  - Boosting, Bagging, Random Forests

Example of a Decision Tree


ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
	categorical	categorical	continuous	class
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Training Data



Model: Decision Tree


Apply Model to Test Data



Test Data

Home Owner	Marital Status	Annual Income	Defaulted Borrower
No	Married	80K	?


Apply Model to Test Data



Test Data

Home Owner	Marital Status	Annual Income	Defaulted Borrower
No	Married	80K	?


Apply Model to Test Data




Test Data

Home Owner	Marital Status	Annual Income	Defaulted Borrower
No	Married	80K	?

Apply Model to Test Data




Apply Model to Test Data



Test Data

Home Owner	Marital Status	Annual Income	Defaulted Borrower
No	Married	80K	?

Apply Model to Test Data




Test Data

Home Owner	Marital Status	Annual Income	Defaulted Borrower
No	Married	80K	?

Assign Defaulted to "No"

Another Example of Decision Tree

	categorical	categorical	continuous	class
ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



There could be more than one tree that fits the same data!


Decision Tree Classification Task

Tid	Attrib1	Attrib2	Attrib3	Class
1	Yes	Large	125K	No
2	No	Medium	100K	No
3	No	Small	70K	No
4	Yes	Medium	120K	No
5	No	Large	95K	Yes
6	No	Medium	60K	No
7	Yes	Large	220K	No
8	No	Small	85K	Yes
9	No	Medium	75K	No
10	No	Small	90K	Yes

Training Set

Tid	Attrib1	Attrib2	Attrib3	Class
11	No	Small	55K	?
12	Yes	Medium	80K	?
13	Yes	Large	110K	?
14	No	Small	95K	?
15	No	Large	67K	?

Test Set




Decision Tree Induction

- Many Algorithms:
  - Hunt's Algorithm (one of the earliest)
  - CART
  - ID3, C4.5
  - SLIQ,SPRINT


General Structure of Hunt's Algorithm

- Let D_t be the set of training records that reach a node t
- General Procedure:
  - If D_t contains records that belong the same class y_t, then t is a leaf node labeled as y_t
  - If D_t contains records that belong to more than one class, use an attribute test to split the data into smaller subsets. Recursively apply the procedure to each subset.

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



Hunt's Algorithm




(7,3)


(a)

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Hunt's Algorithm




(a)




(b)

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Hunt's Algorithm




(a)




(b)

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes




(c)


Hunt's Algorithm




(a)



(b)



(c)



(d)

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Design Issues of Decision Tree Induction

- How should training records be split?
  - Method for expressing test condition
    - depending on attribute types
  - Measure for evaluating the goodness of a test condition


- How should the splitting procedure stop?
  - Stop splitting if all the records belong to the same class or have identical attribute values
  - Early termination

Methods for Expressing Test Conditions


- Depends on attribute types
  - Binary
  - Nominal
  - Ordinal
  - Continuous

Test Condition for Nominal Attributes

- Multi-way split:
  - Use as many partitions as distinct values.




- Binary split:
  - Divides values into two subsets




Test Condition for Ordinal Attributes


- Multi-way split:
  - Use as many partitions as distinct values
- Binary split:
  - Divides values into two subsets
  - Preserve order property among attribute values



Test Condition for Continuous Attributes



(i) Binary split



(ii) Multi-way split

Splitting Based on Continuous Attributes

- Different ways of handling
  - Discretization to form an ordinal categorical attribute


    Ranges can be found by equal interval bucketing, equal frequency bucketing (percentiles), or clustering.
    - Static – discretize once at the beginning
    - Dynamic – repeat at each node

  - Binary Decision: $(A < v)$ or $(A \geq v)$
    - consider all possible splits and finds the best cut
    - can be more compute intensive

How to determine the Best Split

Customer Id	Gender	Car Type	Shirt Size	Class
1	M	Family	Small	C0
2	M	Sports	Medium	C0
3	M	Sports	Medium	C0
4	M	Sports	Large	C0
5	M	Sports	Extra Large	C0
6	M	Sports	Extra Large	C0
7	F	Sports	Small	C0
8	F	Sports	Small	C0
9	F	Sports	Medium	C0
10	F	Luxury	Large	C0
11	M	Family	Large	C1
12	M	Family	Extra Large	C1
13	M	Family	Medium	C1
14	M	Luxury	Extra Large	C1
15	F	Luxury	Small	C1
16	F	Luxury	Small	C1
17	F	Luxury	Medium	C1
18	F	Luxury	Medium	C1
19	F	Luxury	Medium	C1
20	F	Luxury	Large	C1

Before Splitting: 10 records of class 0,
10 records of class 1



Which test condition is the best?

How to determine the Best Split

- Greedy approach:
  - Nodes with purer class distribution are preferred

- Need a measure of node impurity:

C0: 5 C1: 5	C0: 9 C1: 1
High degree of impurity	**Low degree of impurity**

Measures of Node Impurity

- Gini Index

$$Gini\ Index = 1 - \sum_{i=0}^{c-1} p_i(t)^2$$

Where $\boldsymbol{p_i(t)}$ is the frequency of class $\boldsymbol{i}$ at node $\mathbf{t}$, and $\boldsymbol{c}$ is the total number of classes

- Entropy

$$Entropy = -\sum_{i=0}^{c-1} p_i(t) log_2 p_i(t)$$

- Misclassification error

$$Classification\ error = 1 - \max[p_i(t)]$$


Finding the Best Split

1. Compute impurity measure (P) before splitting
2. Compute impurity measure (M) after splitting
   - Compute impurity measure of each child node
   - M is the weighted impurity of child nodes
3. Choose the attribute test condition that produces the highest gain

Gain = P - M

or equivalently, lowest impurity measure after splitting (M)

Finding the Best Split



Measure of Impurity: GINI

- Gini Index for a given node $\boldsymbol{t}$

$$Gini\ Index = 1 - \sum_{i=0}^{c-1} p_i(t)^2$$

Where $\boldsymbol{p_i(t)}$ is the frequency of class $\boldsymbol{i}$ at node $\boldsymbol{t}$, and $\boldsymbol{c}$ is the total number of classes

  - Maximum of $1 - 1/c$ when records are equally distributed among all classes, implying the least beneficial situation for classification
  - Minimum of 0 when all records belong to one class, implying the most beneficial situation for classification
  - Gini index is used in decision tree algorithms such as CART, SLIQ, SPRINT

Measure of Impurity: GINI

- Gini Index for a given node t :

$$Gini\ Index = 1 - \sum_{i=0}^{c-1} p_i(t)^2$$

  - For 2-class problem (p, 1 – p):
    - GINI = $1 - p^2 - (1 - p)^2 = 2p\ (1\text{-}p)$

C1	**0**
C2	**6**
Gini=0.000	

C1	**1**
C2	**5**
Gini=0.278	

C1	**2**
C2	**4**
Gini=0.444	

C1	**3**
C2	**3**
Gini=0.500	

Computing Gini Index of a Single Node

$$Gini\ Index = 1 - \sum_{i=0}^{c-1} p_i(t)^2$$

C1	**0**
C2	**6**

P(C1) = 0/6 = 0 P(C2) = 6/6 = 1

Gini = 1 – P(C1)² – P(C2)² = 1 – 0 – 1 = 0

C1	**1**
C2	**5**

P(C1) = 1/6 P(C2) = 5/6

Gini = 1 – (1/6)² – (5/6)² = 0.278

C1	**2**
C2	**4**

P(C1) = 2/6 P(C2) = 4/6

Gini = 1 – (2/6)² – (4/6)² = 0.444

Computing Gini Index for a Collection of Nodes

- When a node p is split into k partitions (children)


$$GINI_{split} = \sum_{i=1}^{k} \frac{n_i}{n} GINI(i)$$

where, n_i = number of records at child i,

n = number of records at parent node p.

Binary Attributes: Computing GINI Index

- Splits into two partitions (child nodes)
- Effect of Weighing partitions:
  - Larger and purer partitions are sought



	Parent
C1	7
C2	5
Gini = 0.486	

Gini(N1)
= 1 – (5/6)² – (1/6)²
= 0.278

Gini(N2)
= 1 – (2/6)² – (4/6)²
= 0.444

	N1	N2
C1	5	2
C2	1	4
Gini=0.361		

Weighted Gini of N1 N2
= 6/12 * 0.278 +
6/12 * 0.444
= 0.361

Gain = 0.486 – 0.361 = 0.125

Categorical Attributes: Computing Gini Index

- For each distinct value, gather counts for each class in the dataset
- Use the count matrix to make decisions

Multi-way split

	CarType		
	Family	Sports	Luxury
C1	1	8	1
C2	3	0	7
Gini	0.163		

Two-way split
(find best partition of values)

	CarType	
	{Sports, Luxury}	{Family}
C1	9	1
C2	7	3
Gini	0.468	


	CarType	
	{Sports}	{Family, Luxury}
C1	8	2
C2	0	10
Gini	0.167	

Which of these is the best?

Continuous Attributes: Computing Gini Index

- Use Binary Decisions based on one value
- Several Choices for the splitting value
  - Number of possible splitting values = Number of distinct values
- Each splitting value has a count matrix associated with it
  - Class counts in each of the partitions, A ≤ v and A > v
- Simple method to choose best v
  - For each v, scan the database to gather count matrix and compute its Gini index
  - Computationally Inefficient! Repetition of work.

ID	Home Owner	Marital Status	Annual Income	Defaulted
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes




Continuous Attributes: Computing Gini Index...

- For efficient computation: for each attribute,
  - Sort the attribute on values
  - Linearly scan these values, each time updating the count matrix and computing gini index
  - Choose the split position that has the least gini index

Cheat	No	No	No	Yes	Yes	Yes	No	No	No	No
Annual Income										
Sorted Values →	60	70	75	85	90	95	100	120	125	220


Continuous Attributes: Computing Gini Index...

- For efficient computation: for each attribute,
  - Sort the attribute on values
  - Linearly scan these values, each time updating the count matrix and computing gini index
  - Choose the split position that has the least gini index




Continuous Attributes: Computing Gini Index...

- For efficient computation: for each attribute,
  - Sort the attribute on values
  - Linearly scan these values, each time updating the count matrix and computing gini index
  - Choose the split position that has the least gini index



Continuous Attributes: Computing Gini Index...

- For efficient computation: for each attribute,
  - Sort the attribute on values
  - Linearly scan these values, each time updating the count matrix and computing gini index
  - Choose the split position that has the least gini index



Continuous Attributes: Computing Gini Index...

- For efficient computation: for each attribute,
  - Sort the attribute on values
  - Linearly scan these values, each time updating the count matrix and computing gini index
  - Choose the split position that has the least gini index

Cheat	No	No	No	Yes	Yes	Yes	No	No	No	No
Annual Income										
Sorted Values →	60	70	75	85	90	95	100	120	125	220
Split Positions →	55	65	72	80	87	92	97	110	122	172	230
	<= >	<= >	<= >	<= >	<= >	<= >	<= >	<= >	<= >	<= >	<= >
Yes	0 3	0 3	0 3	0 3	1 2	2 1	3 0	3 0	3 0	3 0	3 0
No	0 7	1 6	2 5	3 4	3 4	3 4	3 4	4 3	5 2	6 1	7 0
Gini	0.420	0.400	0.375	0.343	0.417	0.400	***0.300***	0.343	0.375	0.400	0.420

Measure of Impurity: Entropy

- Entropy at a given node $\boldsymbol{t}$

$$Entropy = -\sum_{i=0}^{c-1} p_i(t) log_2 p_i(t)$$

Where $\boldsymbol{p_i(t)}$ is the frequency of class $\boldsymbol{i}$ at node $\boldsymbol{t}$, and $\boldsymbol{c}$ is the total number of classes

  - Maximum of $\log_2 c$ when records are equally distributed among all classes, implying the least beneficial situation for classification
  - Minimum of 0 when all records belong to one class, implying most beneficial situation for classification

- Entropy based computations are quite similar to the GINI index computations

Computing Entropy of a Single Node

$$Entropy = -\sum_{i=0}^{c-1} p_i(t) log_2 p_i(t)$$

C1	**0**
C2	**6**

P(C1) = 0/6 = 0 P(C2) = 6/6 = 1

Entropy = – 0 log 0 – 1 log 1 = – 0 – 0 = 0

C1	**1**
C2	**5**

P(C1) = 1/6 P(C2) = 5/6

Entropy = – (1/6) $\log_2$ (1/6) – (5/6) $\log_2$ (1/6) = 0.65

C1	**2**
C2	**4**

P(C1) = 2/6 P(C2) = 4/6

Entropy = – (2/6) $\log_2$ (2/6) – (4/6) $\log_2$ (4/6) = 0.92

Computing Information Gain After Splitting

- Information Gain:

$$Gain_{split} = Entropy(p) - \sum_{i=1}^{k} \frac{n_i}{n} Entropy(i)$$


Parent Node, p is split into k partitions (children)

n_i is number of records in child node i

  - Choose the split that achieves most reduction (maximizes GAIN)
  - Used in the ID3 and C4.5 decision tree algorithms
  - Information gain is the mutual information between the class variable and the splitting variable

Problem with large number of partitions

- Node impurity measures tend to prefer splits that result in large number of partitions, each being small but pure



  - Customer ID has highest information gain because entropy for all the children is zero

Gain Ratio

- Gain Ratio:

$$Gain\ Ratio = \frac{Gain_{split}}{Split\ Info} \qquad Split\ Info = -\sum_{i=1}^{k} \frac{n_i}{n} log_2 \frac{n_i}{n}$$

Parent Node, p is split into k partitions (children)

n_i is number of records in child node i

  - Adjusts Information Gain by the entropy of the partitioning ($Split\ Info$).
    - Higher entropy partitioning (large number of small partitions) is penalized!
  - Used in C4.5 algorithm
  - Designed to overcome the disadvantage of Information Gain

Gain Ratio

- Gain Ratio:

$$Gain\ Ratio = \frac{Gain_{split}}{Split\ Info} \qquad Split\ Info = \sum_{i=1}^{k} \frac{n_i}{n} log_2 \frac{n_i}{n}$$

Parent Node, p is split into k partitions (children)

n_i is number of records in child node i

	CarType		
	Family	Sports	Luxury
C1	1	8	1
C2	3	0	7
Gini	0.163		

SplitINFO = 1.52

	CarType	
	{Sports, Luxury}	{Family}
C1	9	1
C2	7	3
Gini	0.468	

SplitINFO = 0.72

	CarType	
	{Sports}	{Family, Luxury}
C1	8	2
C2	0	10
Gini	0.167	

SplitINFO = 0.97

Measure of Impurity: Classification Error

- Classification error at a node t

$$Error(t) = 1 - \max_i [p_i(t)]$$

  - Maximum of $1 - 1/c$ when records are equally distributed among all classes, implying the least interesting situation
  - Minimum of 0 when all records belong to one class, implying the most interesting situation

Computing Error of a Single Node

$$Error(t) = 1 - \max_i [p_i(t)]$$

C1	**0**
C2	**6**

P(C1) = 0/6 = 0 P(C2) = 6/6 = 1

Error = 1 – max (0, 1) = 1 – 1 = 0

C1	**1**
C2	**5**

P(C1) = 1/6 P(C2) = 5/6

Error = 1 – max (1/6, 5/6) = 1 – 5/6 = 1/6


C1	**2**
C2	**4**

P(C1) = 2/6 P(C2) = 4/6


Error = 1 – max (2/6, 4/6) = 1 – 4/6 = 1/3

Comparison among Impurity Measures

For a 2-class problem:



Misclassification Error vs Gini Index



	Parent
C1	7
C2	3
Gini = 0.42	

Gini(N1)
= 1 – (3/3)² – (0/3)²
= 0


Gini(N2)
= 1 – (4/7)² – (3/7)²
= 0.489

	N1	N2
C1	3	4
C2	0	3
Gini=0.342		

Gini(Children)
= 3/10 * 0
+ 7/10 * 0.489
= 0.342

Gini improves but error remains the same!!

Misclassification Error vs Gini Index



	Parent
C1	**7**
C2	**3**
Gini = 0.42	

	N1	N2
C1	**3**	**4**
C2	**0**	**3**
Gini=0.342		


	N1	N2
C1	**3**	**4**
C2	**1**	**2**
Gini=0.416		

Misclassification error for all three cases = 0.3 !

Decision Tree Based Classification

- Advantages:
  - Relatively inexpensive to construct
  - Extremely fast at classifying unknown records
  - Easy to interpret for small-sized trees
  - Robust to noise (especially when methods to avoid overfitting are employed)
  - Can easily handle redundant attributes
  - Can easily handle irrelevant attributes (unless the attributes are interacting)
- Disadvantages: .
  - Due to the greedy nature of splitting criterion, interacting attributes (that can distinguish between classes together but not individually) may be passed over in favor of other attributed that are less discriminating.
  - Each decision boundary involves only a single attribute

Handling interactions




+ : 1000 instances

o : 1000 instances


Entropy (X) : 0.99

Entropy (Y) : 0.99

Handling interactions




(a) Decision boundary for tree with 6 leaf nodes.



(b) Decision tree with 6 leaf nodes.

Figure 3.28. Decision tree with 6 leaf nodes using X and Y as attributes. Splits have been numbered from 1 to 5 in order of other occurrence in the tree.

Handling interactions given irrelevant attributes




+ : 1000 instances

o : 1000 instances

Adding Z as a noisy attribute generated from a uniform distribution


Entropy (X) : 0.99
Entropy (Y) : 0.99
Entropy (Z) : 0.98

Attribute Z will be chosen for splitting!



(a) Three-dimensional data with attributes X, Y, and Z.

Limitations of single attribute-based decision boundaries



Both positive (+) and negative (o) classes generated from skewed Gaussians with centers at (8,8) and (12,12) respectively.